

Fixed Speed Cassette Indoor

Q8 Cassette Indoor			TCC-18HRA-4	TCC-24HRA	TCC-36HRSA/S	TCC-48HRSA	TCC-60HRSA
Flow			4-Way	8-Way	8-Way	8-Way	8-Way
Power supply		V/Ph/Hz	220-240V~50Hz/1P	220-240V~50Hz/1P	220-240V~50Hz/1P	220-240V~50Hz/1P	220-240V~50Hz/1P
Cooling	Capacity	BTU/H	18000	24000	36000	48000	60000
	Capacity	W	5100	7200	10500	14000	16000
	Input	W	1683	2432	3750	4636	6000
Heating	Capacity	BTU/H	19000	26500	40000	51200	66000
	Capacity	W	5600	8000	12000	16000	17500
	Input	W	1761	2192	3500	5079	6200
Indoor air flow (Hi/Mi/Lo)		m3/h	800/750/600	1400/1200/950	1700/1500/1400	1700/1500/1400	1900/1700/1500
Indoor noise level (Hi/Mi/Lo)		dB(A)	41/38/34	43/41/37	45/43/41	45/43/41	47/44/43
Indoor unit	Unit (W*D*H)	mm	575x260x575	830x230x830	830x290x830	830x230x830	830x230x830
	Packing (W*D*H)	mm	725x300x725	950x265x950	950x320x950	950x320x950	950x320x950
	Net/Gross weight	Kg	18.5/23	27/30	30/37	30/37	31/38
Panel	Unit (W*D*H)	mm	650x30x650	950x45x950	950x45x950	950x45x950	950x45x950
	Packing (W*D*H)	mm	760x100x760	1035x90x1035	1035x90x1035	1035x90x1035	1035x90x1035
	Net/Gross weight	Kg	2.5/4.5	6/9	6/9	6/9	6/9
Refrigerant pipe	Liquid side/Gas side	mm	(1/4)/(1/2)	(3/8)/(5/8)	(3/8)/(3/4)	(3/8)/(3/4)	(3/8)/(3/4)
Drainage water pipe diameter		mm	OD32	OD32	OD32	OD32	OD32
Refrigerant type			R410A	R410A	R410A	R410A	R410A
Operation temperature range		°C	16~30	16~30	16~30	16~30	16~30
Operation control			Remote controller	Remote controller	Remote controller	Remote controller	Remote controller

Inverter Cassette Indoor

Q8 Cassette Indoor			TCC-18HRA-4I	TCC-24HRAI	TCC-36HRSA/SI	TCC-48HRSAI	TCC-60HRSAI
Flow			4-Way	8-Way	8-Way	8-Way	8-Way
Power supply		V/Ph/Hz	220-240V~50Hz/1P	220-240V~50Hz/1P	220-240V~50Hz/1P	220-240V~50Hz/1P	220-240V~50Hz/1P
Cooling	Capacity	BTU/H	18000	24000	36000	48000	60000
	Capacity	W	5276	7034	10550	14000	17500
	Input	W	1640	2190	3280	4370	5450
	Rated current	A	7.1	9.9	15.0	8.2	9.50
Heating	Capacity	BTU/H	19650	26000	40000	53000	63000
	Capacity	W	5759	7620	11700	15530	18400
	Input	W	1720.00	2360.00	3600	4810	5750
	Rated current	A	7.90	10.6	15.00	9.1	10.10
Indoor air flow (Hi/Mi/Lo)		m3/h	900/800/600	1300/1100/900	1660/1300/1100	1660/1300/1100	1700/1300/1100
Indoor noise level (Hi/Mi/Lo)		dB(A)	41/38/34	44/41/37	45/43/40	47/45/42	50/47/45
Indoor unit	Unit (W*D*H)	mm	575x260x575	830x230x830	830x290x830	830x290x830	830x290x830
	Packing (W*D*H)	mm	725x300x725	950x265x950	950x320x950	950x320x950	950x320x950
	Net/Gross weight	Kg	18.5/23	24/29	30/35	30/35	30/35
Panel	Unit (W*D*H)	mm	650x30x650	950x45x950	950x45x950	950x45x950	950x45x950
	Packing (W*D*H)	mm	760x100x760	1035x90x1035	1035x90x1035	1035x90x1035	1035x90x1035
	Net/Gross weight	Kg	2.5/4.5	6/9	6/9	6/9	6/9
Refrigerant pipe	Liquid side/Gas side	mm	(1/4)/(1/2)	(3/8)/(5/8)	(3/8)/(3/4)	(3/8)/(3/4)	(3/8)/(3/4)
Drainage water pipe diameter		mm	OD32	OD32	OD32	OD32	OD32
Refrigerant type			R410A	R410A	R410A	R410A	R410A
Operation temperature range		°C	16~30	16~30	16~30	16~30	16~30
Operation control			Remote controller	Remote controller	Remote controller	Remote controller	Remote controller