

Fixed Speed Ceiling Floor Indoor

			TUB-18HRA	TUB-24HRA	TUB-36HRSA/S	TUB-48HRSA	TUB-60HRSA
Power supply		V/Ph/Hz	220-240V~50Hz/1P	220-240V~50Hz/1P	220-240V~50Hz/1P	220-240V~50Hz/1P	220-240V~50Hz/1P
Cooling	Capacity	BTU/H	18000	24000	36000	48000	55000
	Capacity	W	5300	7200	10500	14000	16000
	Input	W	1712	2230	3578	4551	5594
Heating	Capacity	BTU/H	20000	26500	40000	50000	60500
	Capacity	W	5862	7767	12000	14654	17732
	Input	W	1782	2254	3468	4432	5147
Indoor air flow (Hi/Mi/Lo)		m3/h	900/800/700	1200/950/770	1700/1300/1100	2177/1689/1434	2455/2393/1330
Indoor noise level (Hi/Mi/Lo)		dB(A)	43/41/38	45/43/40	45/43/40	52/49/46	52/49/46
Indoor unit	Unit (W*D*H)	mm	1055x675x235	1055x675x235	1275x675x235	1635x675x235	1635x675x235
	Packing (W*D*H)	mm	1140x755x313	1140x755x313	1360x755x313	1720x755x313	1720x755x313
	Net/Gross weight	Kg	23/30	24/30	29/35	38/46	38/48
Refrigerant pipe	Liquid side/Gas side	mm	(1/4)/(1/2)	(3/8)/(5/8)	(3/8)/(3/4)	(3/8)/(3/4)	(3/8)/(3/4)
Drainage water pipe diameter		mm	OD25	OD25	OD25	OD25	OD25
Refrigerant type			R410A	R410A	R410A	R410A	R410A
Operation temperature range		°C	16~30	16~30	16~30	16~30	16~30
Operation control			Remote controller	Remote controller	Remote controller	Remote controller	Remote controller

Inverter Ceiling Floor Indoor

			TUB-18HRAI	TUB-24HRAI	TUB-36HRSA/SI	TUB-48HRSAI	TUB-60HRSAI
Power supply		V/Ph/Hz	220-240V~50Hz/1P	220-240V~50Hz/1P	220-240V~50Hz/1P	220-240V~50Hz/1P	220-240V~50Hz/1P
Cooling	Capacity	BTU/H	18000	24000	36000	48000	60000
	Capacity	W	5274	7034	10550	14000	17500
	Input	W	1635	2180	3280	4370	5460
	Rated current	A	7.2	9.9	15.0	8.20	9.50
Heating	Capacity	BTU/H	19800	26000	40000	53000	63000
	Capacity	W	5800	7620	11700	15530	18400
	Input	W	1810.00	2350.00	3600	4810	5750
	Rated current	A	8.1	10.6	15.5	9.10	10.10
Indoor air flow (Hi/Mi/Lo)		m3/h	1100/860/700	1300/1050/900	1500/1250/1050	1800/1550/1250	1950/1770/1450
Indoor noise level (Hi/Mi/Lo)		dB(A)	43/40/36	45/41/37	46/44/42	52/49/46	55/51/48
Indoor unit	Unit (W*D*H)	mm	1055x675x235	1055x675x235	1275x675x235	1635x675x235	1635x675x235
	Packing (W*D*H)	mm	1131x753x313	1131x753x313	1351x753x313	1711x753x313	1711x753x313
	Net/Gross weight	Kg	23/28	27/32	30/36	39/46	41/48
Refrigerant pipe	Liquid side/Gas side	mm	(1/4)/(1/2)	(3/8)/(5/8)	(3/8)/(3/4)	(3/8)/(3/4)	(3/8)/(3/4)
Drainage water pipe diameter		mm	OD32	OD32	OD25	OD25	OD25
Refrigerant type			R410A	R410A	R410A	R410A	R410A
Operation temperature range		°C	16~30	16~30	16~30	16~30	16~30
Operation control			Remote controller	Remote controller	Remote controller	Remote controller	Remote controller