

Fixed Speed MESP Ducted Indoor

			TTB-18HWA	TTB-24HWA	TTB-36HWSA/S	TTB-36HWSA	TTB-48HWSA	TTB-60HWSA
Power supply		V/Ph/Hz	220-240V~50Hz/1P	220-240V~50Hz/1P	220-240V~50Hz/1P	220-240V~50Hz/1P	220-240V~50Hz/1P	220-240V~50Hz/1P
Cooling	Capacity	BTU/H	18000	24000	36000	36000	48000	60000
	Capacity	W	5300	7200	10500	10500	14000	16000
	Input	W	1761	2315	3710	3584	4950	6500
Heating	Capacity	BTU/H	20000	26500	40000	40000	51500	66000
	Capacity	W	5900	8000	12000	12000	16000	17500
	Input	W	1513	2388	3510	3468	5200	6800
Indoor air flow (Hi/Mi/Lo)		m3/h	1170/770/650	1500/950/800	2270/1890/1650	2270/1890/1650	3010/2410/1940	3200/2600/2030
Indoor external static pressure (Hi)		Pa	70	70	80	80	100	100
Indoor noise level (Hi/Mi/Lo)		dB(A)	43/35/32	45/42/40	46/44/42	46/44/42	47/44/42	47/45/43
Indoor unit	Unit (W*D*H)	mm	920x210x605	920x270x605	1140x270x745	1140x270x745	1200x300x835	1200x300x835
	Packing (W*D*H)	mm	1115x280x690	1115x340x690	1345x360x830	1345x360x830	1405x390x925	1405x390x925
	Net/Gross weight	Kg	23/28	25/32	35/40	35/40	45/52	48/54
Refrigerant pipe	Liquid side/Gas side	mm	(1/4)/(1/2)	(3/8)/(5/8)	(3/8)/(3/4)	(3/8)/(3/4)	(3/8)/(3/4)	(3/8)/(3/4)
Drainage water pipe diameter		mm	OD25	OD25	OD25	OD25	OD25	OD25
Refrigerant type			R410A	R410A	R410A	R410A	R410A	R410A
Operation temperature range		°C	16~30	16~30	16~30	16~30	16~30	16~30
Operation control			Wire controller	Wire controller	Wire controller	Wire controller	Wire controller	Wire controller

Inverter MESP Ducted Indoor

			TTB-18HWA I	TTB-24HWA I	TTB-36HWSA/S I	TTB-48HWSA I	TTB-60HWSA I
Power supply		V/Ph/Hz	220-240V~50Hz/1P	220-240V~50Hz/1P	220-240V~50Hz/1P	220-240V~50Hz/1P	220-240V~50Hz/1P
Cooling	Capacity	BTU/H	18000	24000	36000	48000	60000
	Capacity	W	5274	7034	10550	14000	17500
	Input	W	1635	2180	3280	4370	5460
	Rated current	A	7.2	9.9	15	8.20	9.50
Heating	Capacity	BTU/H	19800	26000	40000	53000	63000
	Capacity	W	5800	7620	11700	15530	18400
	Input	W	1810.00	2350.00	3600	4810	5750
	Rated current	A	8.1	10.6	15.5	9.10	10.10
Indoor air flow (Hi/Mi/Lo)		m3/h	1100/950/700	1300/1100/900	1650/1450/1050	1900/1700/1250	2200/1800/1500
Indoor external static pressure (Hi)		Pa	40	50	80	100	100
Indoor noise level (Hi/Mi/Lo)		dB(A)	43/40/36	46/41/37	47/44/40	53/47/44	55/49/46
Indoor unit	Unit (W*D*H)	mm	920x210x605	920x270x605	1140x270x745	1200x300x835	1200x300x835
	Packing (W*D*H)	mm	1115x280x690	1115x340x690	1345x360x830	1405x390x925	1405x390x925
	Net/Gross weight	Kg	23/28	27/32	36/43	44/52	45/55
Refrigerant pipe	Liquid side/Gas side	mm	(1/4)/(1/2)	(3/8)/(5/8)	(3/8)/(3/4)	(3/8)/(3/4)	(3/8)/(3/4)
Drainage water pipe diameter		mm	OD32	OD32	OD25	OD25	OD25
Refrigerant type			R410A	R410A	R410A	R410A	R410A
Operation temperature range		°C	16~30	16~30	16~30	16~30	16~30
Operation control			Wire controller	Wire controller	Wire controller	Wire controller	Wire controller